




P4000 Sky | Pendant & Surface Semi-Recessed




PRUDENTIAL LTG.

PRULITE.COM 213.746.0360



Type:

Job:



Break the plane for dramatic effect.

Another Prudential Ltg. first, merging our ever-popular P4000 pendant with a hard ceiling trimless flange. The P4000 can be tilted up to 15° for a fun, playful effect or just semi-recessed into the ceiling at different heights — easily adjustable by locking wingnuts.

P4030-LED35-SO-FWA

11889 Delivered Lumens

113 Watts

106 lm/w



LUMEN OUTPUT: Direct (D1)

	LO	MO	SO	HO
18" Im/w	950	1650	1950	2150
	19	33	39	47
2' Im/w	2100	3150	3900	5300
	35	54	67	97
3' Im/w	5800	9100	11889	17700
	56	87	113	177
4' Im/w	9200	11500	18200	28000
	88	110	174	281



Lumen output may vary +/- 5% 3500K used for lm/ft estimates above 4000K +2% llf, 3000K -2%, 2700K -4% -10% LLF for 90 CRI (4K, 3500K and 3K)

See LED Details PDF for more info

SERIES	LED COLOR	OUTPUT	SHIELD-ING	COLOR/FINISH	CEILING TRIM	DISTRI-BUTION	CIRCUIT-ING	VOLTAGE	PLENUM DEPTH	CEILING SYSTEMS	DRIVERS	OPTIONS
P4018 18" Dia. (11 lbs)	LED27 2700K (90CRI)	LO Low	FWA Flat White Acrylic Lens	TMW Textured Matte White	YBK Interior Matte Black Matte (Standard)	D1 Direct	SC Single Circuit	UNV (120-277)	SMR7 7" Plenum Semi- Recessed (Standard)	X1 T-Bar (9/16" or 15/16" T-Bar, Armstrong Interlude or slot grid)	ND Non-Dimming DM10 0-10v, 10% Dimming (Standard) DM01 0-10v, 1% Dimming	EML Emergency Battery, Low (P4018: 400; P4020: 500; P4030 & P4040: 900 delivered lumens)
P4020 2" Dia. (22 lbs)	LED3 3000K	SO Standard	VWA Convex White Acrylic Lens (1" Max drop)	YGW Gloss White (Standard)	TMW Textured Matte White (Recommended for t-bar installs)			347 (Emergency battery requires a Step Down transformer)	SMR4 4" Plenum Semi- Recessed	X7 Hard Ceiling (Hard ceiling mud over flange)	STEP Step Dimming, 100-50-Off, Osram NOTE: Lumens and watts per foot may differ for STEP drivers, consult factory	EMH Emergency Battery, High (NA - 18" & 2"; P4030 & P4040: 1250 delivered lumens)
P4030 3" Dia. (35 lbs)	LED35 3500K	HO High		Y_ Premium Color							LDE5 5-Series EcoSystem LED LDE1 Hi-lume 1% EcoSystem LED (Soft fade on, fade-to-black dimming)	PRUBIN Meticulous Binning and Labeling every LED board within a 2-step MacAdams Ellipse
P4040 4" Dia. (50 lbs)	LED4 4000K	PROG Pro- gram- mable Light Output (Specify desired lm or w/ fixture)		CC Custom Color	YGW Gloss White						LTE Hi-lume 1% 2-wire LED Driver (120V forward phase only) ECO 1% 0-10v, EldoLED ECDA 1% DALI, EldoLED SOLO 0.1% 0-10v, EldoLED (Dim to Dark) SODA 0.1% DALI, EldoLED (Dim to Dark)	
	LED3-90 90CRI				Y_ Premium Color							
	LED35-90 90CRI				CC Custom Color							
	LED4-90 90CRI				Y_ Premium Color							
					CC Custom Color							



P4000 Sky | Pendant & Surface Semi-Recessed



PRUDENTIAL LTG.

PRULITE.COM 213.746.0360

D1

Standard Output:

P4030-LED35-SO-VWA-D1


11889 Delivered Lumens

113 Watts

106 lm/w

3500 CCT

Test #L031511001



Zonal Lumen Summary:

0-90 = 100%

4543

Vertical Angle	0°	25°	45°	65°	90°
0°	4543	4543	4543	4543	4543
5°	4524	4524	4524	4524	4524
15°	4353	4353	4353	4353	4353
25°	4034	4034	4034	4034	4034
35°	3584	3584	3584	3584	3584
45°	2935	2935	2935	2935	2935
55°	2081	2081	2081	2081	2081
65°	1282	1282	1282	1282	1282
75°	527	527	527	527	527
85°	126	126	126	126	126
90°	0	0	0	0	0

Luminance Chart:

Angle	0°	45°	90°
45°	6487	6487	6487
55°	5670	5670	5670
65°	4741	4741	4741
75°	3182	3182	3182
85°	2259	2259	2259

LUMEN MAINTENANCE

Designed to last with cool running mid-power LEDs projected to maintain 90% (L90) of their initial output for 100,000 hours (at HO), and L70 exceeding 150,000 hours.

LED SYSTEM

LED modules and drivers are field replaceable.

PROG

(OPTIONAL)

Programmable light output. Specify desired lumens or watts per fixture.

BINNING

Standard binning (all Prudential LED boards) includes testing at the chip level and board integration to provide consistent color temperature within a 3-step MacAdams ellipse, with +/- 5% lumen output range and +/- .004 Duv.

PRUBIN™

(OPTIONAL)

Prudential Ltg's exclusive 'job binning' method that ensures color temperature consistency across all luminaires on a project. Meticulously testing and labeling **EVERY LED BOARD** to +/- 25 lumens, +/- 50k CCT and +/- .004 Duv — while also separating positive from negative — allows us to match color, hue and intensity throughout a project and provides a consistent color temperature within a 2-step MacAdams ellipse

LABELS

ETL damp labeled and I.B.E.W. manufactured.

ELECTRICAL

Must specify LED dimming controls. LED fixtures have constant current driver(s) with less than 20% THD when loaded to a minimum of 60%. Drivers sink a maximum of 6mA per driver. DM10 LED drivers are 0-10V dimmable and are compatible with most 0-10V wall slide dimmers and direct 0-10V analog signal dimmers. Max driver size 2.38" w x 1.5" h.

CONSTRUCTION

Housing

Extruded aluminum, rolled and welded, >25% PC recycled, 100% recyclable

Lens

Flat or convex (subtle drop mitigates lamp image) acrylic, 100% recyclable

MOUNTING

Semi-recessed

WARRANTY

Single-source, 5 year limited warranty covers standard components and construction.



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data. © 2014 All rights reserved - All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Sky Oculus Series

2

02-27-2019



P4000 Sky | Pendant & Surface Semi-Recessed



PRUDENTIAL LTG.


PRULITE.COM 213.746.0360

YSW – Seashell White (Matte)	YCH – Champagne (Metallic)
YSL – Silver (Metallic)	YPE – Pewter (Matte)
YRG – Rain Grey (Gloss)	YSTM – Storm Grey (Matte)
YBK – Black (Matte)	YBB – Black (Semi Gloss)
YSKM – Sky (Matte)	YMB – Military Blue (Matte)
YIB – Interstate Blue (Matte)	YSAM – Sapphire (Matte)
YFGM – Forest Green (Matte)	YBR – Bronze (Matte)
YBY – Boysenberry (Matte)	YSRM – Sunset Red (Matte)
YOR – Orange (Matte)	YDAM – Daffodil (Matte)



Client | DC Comics Architect | Beckson Design Associates


MOUNTING LOCATIONS



Choose from one of our Premium Colors with no set-up fee.

For paint chip samples, please email: info@prulite.com

TILT:



SMR - Semi Recessed up to 10.5° tilt Trimless
X7 mud-over flange for hard ceilings

COMPLIMENTARY FIXTURES



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved - All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058



P4000 Sky | Pendant & Surface Semi-Recessed




PRUDENTIAL LTG.


PRULITE.COM 213.746.0360

T-BAR ASSEMBLIES


P4018




P4020



P4040



P4030



Prudential Ltg. reserves the right to change design specifications or materials without notice. Please visit prulite.com for most current data.
© 2014 All rights reserved - All products manufactured at: Prudential Ltg. 1774 E. 21st Street, Los Angeles, CA 90058

Sky Oculus Series

4

02-27-2019